

INFOCUS IN32

Display

Native Aspect Ratio:	4x3
Supported Aspect Ratio:	16:9, 4:3, 5:4
Brightness: (max ANSI lumens)	High Bright: 2000 Lumens Eco Mode: 1600 Lumens
Contrast Ratio:	1000 : 1 Full On/Full Off
Display Technology:	DLP® by Texas Instruments™: 0.7" XGA DDR DMD
Data Compatibility:	VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), SXGA (1400x1050)
Video Compatibility:	Full NTSC, PAL, SECAM, 480i, 576i, 480p, 576p, 720p, 1080i
Color Wheel (DLP Only):	4-segment, 2-speed
Native Resolution:	XGA
Projector Placement:	Ceiling Projection, Front Projection, Rear Projection
SMPTE Brightness:	Not Available
Lamp Wattage:	High Bright: 200 Watts Eco Mode: Not Available
Lamp Life:	High Bright: 2000 Hours Eco Mode: Not Available
Minimum Image Size:	2.7 ft (0,82 m)
Maximum Image Size:	22 ft (6,71 m)
Standard Lens Zoom:	1.2 : 1
Standard Lens Throw Ratio:	1.83 - 2.27 (Distance/Width)
Standard Lens Image Offset Ratio:	115%
Standard Lens Projection Distance:	4.9 - 32.8 ft (1,49 - 10 m)
Digital Keystone Correction (Vertical):	+30°/-25°
Digital Keystone Correction (Horizontal):	Not Available
Lens Shift:	Not Available

Inputs and Outputs

DVI:	Number of Inputs: 1 Requires M1 to DVI cable (SP-DVI-D)
M1:	Number of Inputs: 1 Accepts digital and analog computer and video signals.
HDMI:	Not Available
BNC:	Not Available
Component (RCA):	Number of Inputs: 1 480i/480p requires VESA to Component cable or M1 to Component cable.
VESA (HD15):	Number of Inputs: 1 15-pin analog
S-Video:	Number of Inputs: 1 4-pin mini-DIN
Composite (RCA):	Number of Inputs: 1
Standard Definition TV:	Composite RCA, S-Video
Enhanced Definition TV:	VGA, M1-DA
High Definition TV:	VGA, M1-DA
Computer:	VGA, M1-DA

HDCP Support:	No
Stereo RCA Jacks Inputs:	No
Stereo 3.5 mm Mini-jack Inputs:	Yes
12v trigger for motorized screens (3.5 mm mini-jack):	No
Projector Control:	Projector Keypad, Remote
Speakers:	3.0 Watt mono speaker
Monitor Output:	Yes
Audio Output:	3.5mm mini-jack for computer and video

Compatibility

Data Compatibility:	VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), SXGA (1400x1050)
H-Sync Range:	15.6 - 85kHz
V-Sync Range:	48 - 85Hz
Video Compatibility:	Full NTSC, PAL, SECAM, 480i, 576i, 480p, 576p, 720p, 1080i

General

Audible Noise:	35 dB
Actual Dimensions:	Height: 2.9 in (7,37 cm) Length: 8.6 in (21,84 cm) Width: 10.4 in (26,42 cm)
Actual Weight:	5 lbs (2,27 kg)
Shipping Dimensions:	Height: 8 in (20,32 cm) Length: 20 in (50,8 cm) Width: 15 in (38,1 cm)
Shipping Weight:	10 lbs (4,54 kg)
Projector Warranty:	3 Years Door-Step Swap
Lamp Warranty:	1 year
Accessories Warranty:	90 days
Operating temperature: (at sea level)	50 - 95° F (10 - 35° C)
Maximum Altitude Supported:	7500 ft (2286 m)
Typical Power Consumption:	260 Watts
Maximum Power Consumption:	Not Available
Power Supply:	100 - 240 Volts at 50 - 60 Hz
Menu Languages:	English, German, French, Italian, Spanish, Norwegian, Portuguese, Simplified Chinese
Approvals:	UL and c-UL (US/Canada), FCC-A (US/Canada), CE (CE member countries), GOST (Russia), TUV GS (Germany), CCC (China), IRAM (Argentina), NOM (Mexico), C-Tick (Australia)

www.lampe-videoprojecteur.info